



Corlo Touch Touch Switch and Display for









Corlo Touch Touch Switch and Display for

Touch Switch for Illumination, Blinds, Scenes ... Switches when the surface is touched or on approach.

Operating Panel for Room Automation

Graphical menus for setting of shading, ventilation and room conditions. Automatic functions can be configured in the ETS, too.

Info Screen for Messages and Measured Values

Display of current weather data, room data or messages from the KNX bus system.

Display for Pictures

High-resolution 3.5 inch display. Brightness sensor for automatic adjustment of the display to ambient brightness.



elektronik

Corlo adapts to the room

- _ Frame chrome-plated matt-finished or glossy
- _ Frame illumination with selectable colour (RGB)
- _ Glass display unit white or black

Corlo is easy to install

- _ Installation in a standard switch socket
- _ Operating voltage 12...40 V DC
- _Corlo Push Buttons and Corlo Power Outlet available to complement the system

Corlo is intelligent

- _ Automatic for ventilation
- _ Automatic for shading (sun protection/screen)
- _ Control of ambient climate (heating, cooling)

Corlo communicates flexibly

- _ KNX connection for data transmission
- _ 4 inputs for binary contact or temperature sensor
- _ Micro SD card slot and USB interface
- _ WLAN connection optional
- _ Access to selected external pages (via WLAN)







FR. 22.03.13	9:24				
-	d	LIGHT HALL		+	I
•	WI	NDOW GALL	ERY	+	I
	Page 5	Page 6	Page 7	\triangleright	

