

DALI REP LI | Signal repeaters for LMS



Areas of application

- Device for luminaire installation

Product benefits

- The ECGs connected to the repeater operate as a group
- Can be addressed via DALI
- Cascadable

Product features

- Expansion of DALI systems by 64 ECGs each time
- Extends the DALI line by 300 m
- Touch DIM control of 64 DALI ECGs
- Maximum power input: 4 W

Technical data

Electrical data

Nominal voltage	100...240 V
Mains frequency	50/60 Hz
System wattage	5.00 W

Dimensions & weight



Length	189.0 mm
Width	30.0 mm
Height	21.0 mm
Product weight	69.00 g
Mounting hole spacing, length	180.0 mm

Temperatures & operating conditions

Ambient temperature range	0...+50 °C
---------------------------	------------

Capabilities

Dimming interface	DALI
Number of control outputs	1
Type of installation	Luminaire integration

Certificates & standards






Type of protection	IP20
Protection class	II

Equipment / Accessories

- Independent installation in connection with LMS CI BOX

Product datasheet

Download Data

File	
	Brochures Non-system-specific components brochure
	Declarations of conformity Declaration of conformity DALI Repeater
	Operating instructions DALI REPEATER LI OPERATING INSTRUCTION (GB)
	CAD data 3-dim DIM MULTI 3 DALI REP LI DALI MULTI 3 DALI EASY III TOUCH DIM RC
	CAD data PDF DALI MULTI 3 DALI EASY III DIM MULTI 3 DALI REP LI

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321292599		Shipping carton box 25	232 mm x 225 mm x 196 mm	10.23 dm ³	2755.60 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.