

Door/window flush-mounted contact in aluminium or wooden ZACWDF1W / ZACWDF1B / ZACWDF1G

Technical Documentation


FEATURES


- Flush-mounted in doors and windows.
- Built in ABS.
- Available colours:
 - White (ref. ZACWDF1W)
 - Black (ref. ZACWDF1B)
 - Grey (ref. ZACWDF1G)

Dimensions Magnet: Ø11 x 19 mm
Contact: Ø11 x 28 mm

- Normally-open contact (when the magnet is not present).
- Conformity with the CE, UKCA directives (marks on packaging).







ASSEMBLY DIAGRAM

- Drill a ø9mm hole on the edge of the door and fit the magnet in by means of pressure.
- 2. Drill another ø9mm hole on the door frame in front of the previous one.
- 3. Recover the wiring through the frame hole and connect it to the device.
- 4. Fit the contact in the door frame by means of pressure.
- Check that the contact works correctly by measuring the continuity while opening/closing the door.






Figure 1. Magnetic contact

DIMENSIONS (mm)







SAFETY INSTRUCTIONS

- Installation should only be performed by qualified professionals according to the laws and regulations applicable in each country.
- Keep the device away from water and do not cover it with clothes, paper or any other material while in use. It must not be hit.
- The WEEE logo means that this device contains electronic parts and it must be properly disposed of by following the instructions at http://zennio.com/weee-regulation.